**Style:**

005-End Cap

005WH-End Cap with Hole

**Size:** DN32-DN300(1 1/4"-12")-005

DN50-DN300(2"-12")-005WH

Max Work Pressure: 2.5MPa(350psi)**Approvals:** FM,UL**Material Specifications****Fittings:**

Ductile iron conforming to ASTM A536, Grade 65-45-12, other material also available, please consult VISION.

Coating:


Orange-Standard

Red- Optional

Hot-Dipped, Zinc Galvanized-Optional

End Cap Style 005

VISION



规格		005型 盲片	
公称直径	实际外径	CE	约重
mm	mm	mm	kg
Inches	Inches	Inches	Lbs.ft
32	42.4	23	0.1
1¼	1.66	0.90	0.2
40	48.3	23	0.2
1½	1.9	0.90	0.4
50	60.3	25	0.2
2	2.375	1.00	0.4
65	73.0	25	0.3
2½	2.875	1.00	0.7
65	76.1	25	0.3
3OD	3.000	1.00	0.7
80	88.9	25	0.4
3	3.500	1.00	0.9
100	108.0	25	0.5
4¼OD	4.250	1.00	1.1
100	114.3	25	0.5
4	4.500	1.00	1.1
125	133.0	25	0.8
5¼OD	5.250	1.00	1.8
125	139.7	25	0.9
5½OD	5.500	1.00	2.0
125	141.3	25	0.9
5	5.563	1.00	2.0
150	159.0	25	1.3
6¼OD	6.250	1.00	2.9
150	165.1	25	1.4
6½OD	6.500	1.00	3.1
150	168.3	25	1.4
6	6.625	1.00	3.1
200A	216.3	31	3.7
8	8.500	1.22	8.2
200	219.1	31	3.8
8	8.625	1.22	8.4



Shanghai Vision Mechanical Joint Ltd., Co.,


Address: Jinlan Rd. 221, Jiading Industrial Park, Shanghai, China

Tel: 0086-21-5954-6862, 5954-6811, Fax: 0086-21--5954-3888 Web: www.visionmfr.com

D-1026E

End Cap with Hole Style 005WH

VISION



规格		005WH型 带孔盲片			
公称直径	实际外径	T	t	h	约重
mm	mm	mm	mm	mm	kg
Inches	Inches	Inches	Inches	Inches	Lbs.ft
50	60.3	28	25	7	0.3
2	2.375	1.10	1.00	0.28	0.7
65	73.0	28	25	13	0.4
2½	2.875	1.10	1.00	0.49	0.9
65	76.1	28	25	14	0.4
3OD	3.000	1.10	1.00	0.55	0.9
80	88.9	28	25	20	0.5
3	3.500	1.10	1.00	0.81	1.1
100	108.0	28	25	30	0.7
4¼OD	4.250	1.10	1.00	1.18	1.5
100	114.3	28	25	35	0.7
4	4.500	1.10	1.00	1.38	1.5
125	133.0	28	25	42	0.9
5¼OD	5.250	1.10	1.00	1.65	2.0
125	139.7	28	25	45	0.9
5½OD	5.500	1.10	1.00	1.79	2.0
125	141.3	28	25	46	0.9
5	5.563	1.10	1.00	1.82	2.0
150	159.0	28	25	55	1.4
6¼OD	6.250	1.10	1.00	2.15	3.1
150	165.1	28	25	58	1.5
6½OD	6.500	1.10	1.00	2.26	3.3
150	168.3	28	25	59	1.5
6	6.625	1.10	1.00	2.32	3.3
200	219.1	44	31	80	4.2
8	8.625	1.75	1.22	3.15	9.3
250	273.0 ^{SW}	44	31	109	14.8
10	10.750 ^{SW}	1.75	1.22	4.27	32.6
300	323.9 ^{SW}	44	31	132	21.0
12	12.750 ^{SW}	1.75	1.22	5.19	46.3



Shanghai Vision Mechanical Joint Ltd., Co.,

Address: Jinlan Rd. 221, Jiading Industrial Park, Shanghai, China

Tel: 0086-21-5954-6862, 5954-6811, Fax: 0086-21--5954-3888 Web: www.visionmfr.com

D-1026E